

Installation Instructions

2015–2022 Ford F-150 Supercab *and* 2017–2022 Ford F-250 to F-550 Super Duty Supercab *Underseat Storage*


Fits DU-HA Part Numbers 20106 20107

Installation Instructions:


Flip up the seat bottoms of the back seats.


Factory Divider

Using an 8mm socket remove the top two bolts from the factory storage divider (as shown by arrows in picture 1). Note: Some models do not have the factory divider or bolts. Refer to following page on how to create threads so you can use the knobs for installation. Some trucks have a vinyl floor which makes the DU-HA sit lower see following page for further instructions.



4 Secure the DU-HA (A) in the truck using the knobs (D), insert the knob through the slot in the back of the DU-HA and thread into the holes from the previously removed bolts.











Safety Instructions:

Warning: Seat bottoms must be down at all times while vehicle is moving. Make sure the DU-HA is secured in the vehicle according to installation instructions. Do not store explosives or hazardous materials in the DU-HA. Do not place loaded guns in the DU-HA.

For further instructions refer to truck owners manual or contact DU-HA, Inc.



Part	Part #	Description	Qty
Α		DU-HA Storage Unit	1
В	Divider-20106	Foam Organizer / Gun Rack	2
С	Divider-20106	Plastic Stiffener	4
D	1001043	Knob	2
Ε	1001201	Nut – M6	2
F	1001155	Washer – M6	2
G	1001102	Rolt _ M6 Tantite	1



This is how the DU-HA should look installed under the back seat.

(A)





Installation Instructions

2015–2022 Ford F-150 Supercab *and* 2017–2022 Ford F-250 to F-550 Super Duty Supercab *Underseat Storage*

Fits DU-HA Part Numbers 20106 20107

Installation Instructions: (Create Threads)

- 6 If your truck did not come with the factory divider as shown in picture 6 follow these steps to create the threads in the top holes of the factory seat brackets so you can use the supplied knobs to install your DU-HA.
- Using a 10mm socket and a drill or impact driver take the supplied M6-1.0 metric bolt (G) and drive it in and out of the top holes of the factory seat brackets. The bolt is a self-threading bolt that will create the threads needed so you can use the knobs to secure your DU-HA in your truck. Once you have created the threads make sure the knob will thread in and out of the holes. If it seems tight you can run the bolt in and out of the holes again. Be careful not to cross thread if you do run the bolt in and out again, start bolt by hand. Once you have verified the knobs thread properly, return to the previous page to step 3 to continue the installation of your DU-HA.





8 Some models of trucks have a vinyl floor and do not have the factory divider. To install the DU-HA in this type of truck set the DU-HA under the rear seat and position it so the slots are facing the back of the truck and line up with the larger middle hole and slot in the seat brackets. Next use the provided M6 knobs, M6 washers and M6 nuts to secure the DU-HA to the seat brackets.











