

BRK2512


BLUE OX® Patriot® Adjustable/Locking Brake Claw **Operating Instructions**





To Open:

1. Place your thumb on top of the claw and place your pointer finger under the back ledge (right). Pinch your fingers together until the claw locks in place (left).




To Close:

- 2. Position the claw onto the brake pedal. NOTE: You can adjust the size of the claw by changing where the top fangs are mounted.
- 3. Press the button on top of the claw to close the claw or push the front button against the brake pedal.
- Caution: Make sure your fingers are not between the upper and lower half of the claw when you press the button.

To Lock:

4. If the claw is open, you can turn the knob one quarter turn to the left to lock it open.

If the claw is closed, you can turn the knob one quarter turn to the left to prevent it from locking open. If the claw is locked, turn the knob one quarter turn to the right to unlock it.



BRK2512 Patriot® Adjustable/Locking Brake Claw Operating Instructions

CUSTOMER SERVICE COMMITMENT

Blue Ox® is committed to providing you with exceptional customer care throughout your lifetime with our products. Our team is here to assist you with any questions you may have regarding the performance of your product. Simply call (402) 385-3051 and you can speak with our customer care team.

Additionally, please visit our website to see which rallies our Destination America team will be attending. For a nominal fee, our service technician will service your towing system to ensure it's in proper working condition. Also, as a commitment to our customers, should you visit our factory, you can stay at our full service Blue Ox® campground at no charge along with enjoying a factory tour.

Again, thank you for being our customer and for the confidence you have shown in the performance of our products. It is because of customers like you we enjoy the success we have today.