

# SAFETY DATA SHEET

Issuing Date 06-Feb-2019

Revision Date 15-June 2020

Revision Number 4



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publicly available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance, and format of this SDS is © 2014 UL LLC. All rights reserved.

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

### Product identifier

Product Name VP Chain Cleaner (VP7920020)

### Other means of identification

Synonyms None

### Recommended use of the chemical and restrictions on use

Recommended Use Electrical / Electronic / Conformal Coating - Aerosol

Uses advised against No information available

### Details of the supplier of the safety data sheet

Supplier Name Maverick Performance Products

Supplier Address 5950 S Cooper Road  
Chandler, AZ. 85249

Supplier Phone Number Phone: (480) 621-7302

### Emergency telephone number

INFOTRAC North America (480) 621-7302

INFOTRAC International (480) 621-7302

Company Emergency Phone Number (480) 621-7302

## 2. HAZARDS IDENTIFICATION

### Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200).


Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Reproductive Toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2



Aspiration toxicity	Category 1
Flammable Aerosols	Category 1
Gases under pressure	Liquefied gas

**GHS Label elements, including precautionary statements**

**Emergency Overview**

<b>Signal word</b>	<b>Danger</b>		
<b>Hazard Statements</b>	Causes skin irritation Causes serious eye irritation Suspected of damaging fertility or the unborn child May cause drowsiness or dizziness May cause damage to organs through prolonged or repeated exposure May be fatal if swallowed and enters airways Extremely flammable aerosol Contains gas under pressure; may explode if heated		
			
<b>Appearance</b>	Clear	<b>Physical state</b>	Liquid spray Aerosol
			<b>Odor</b> Aliphatic hydrocarbons

**Precautionary Statements - Prevention**

- Obtain special instructions before use
- Do not handle until all safety precautions have been read and understood
- Use personal protective equipment as required
- Wash face, hands and any exposed skin thoroughly after handling
- Use only outdoors or in a well-ventilated area
- Do not breathe dust/fume/gas/mist/vapors/spray
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
- Pressurized container: Do not pierce or burn, even after use
- Do not spray on an open flame or other ignition source
- Wear eye/face protection

**Precautionary Statements - Response**

- IF exposed or concerned: Get medical advice/attention
- Specific treatment (see supplemental first aid instructions on this label)

**Eyes**

- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- If eye irritation persists: Get medical advice/attention

**Skin**

- IF ON SKIN: Wash with plenty of soap and water
- If skin irritation occurs: Get medical advice/attention
- Take off contaminated clothing and wash before reuse



**Inhalation**

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

**Ingestion**

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
Do NOT induce vomiting

**Precautionary Statements - Storage**

Store locked up  
Store in a well-ventilated place. Keep container tightly closed  
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F  
Protect from sunlight

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

Not applicable

**Unknown Toxicity**

8 % of the mixture consists of ingredient(s) of unknown toxicity

**Other information**

Toxic to aquatic life with long lasting effects  
PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION

**Interactions with Other Chemicals**

Use of alcoholic beverages may enhance toxic effects.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No.	Weight-%	Trade Secret
Hexanes	110-54-3	30 - 60	*
Acetone	67-64-1	30 - 60	*
Carbon Dioxide	124-38-9	5 - 10	*
Cyclohexane	110-82-7	1 - 5	*

\*The exact percentage (concentration) of composition has been withheld as a trade secret

### 4. FIRST AID MEASURES

**First aid measures****General Advice**

Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.

**Eye contact**

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists. Do not rub affected area.

**Skin contact**

In case of contact with liquefied gas, thaw frosted parts with lukewarm water.



<b>Inhalation</b>	Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, (trained personnel should) give oxygen.
<b>Ingestion</b>	Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Aspiration hazard if swallowed - can enter lungs and cause damage. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Call a physician or poison control center immediately.
<b>Self-protection of the first aider</b>	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

**Most important symptoms and effects, both acute and delayed**

<b>Most Important Symptoms and Effects</b>	Burning sensation. Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.
--	--

**Indication of any immediate medical attention and special treatment needed**

<b>Notes to Physician</b>	Treat symptomatically.
---------------------------	------------------------

**5. FIRE-FIGHTING MEASURES**

**Suitable Extinguishing Media**

Use extinguishing agent suitable for type of surrounding fire. Water spray, fog or regular foam. Move containers from fire area if you can do it without risk. Damaged cylinders should be handled only by specialists. Dry chemical, CO2, alcohol-resistant foam or water spray.

**Unsuitable extinguishing media**

DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.

**Specific hazards arising from the chemical**

Some may burn but none ignite readily. Ruptured cylinders may rocket.

<b>Uniform Fire Code</b>	Irritant: Liquid Aerosols: Level III
--------------------------	---

**Hazardous Combustion Products**

Carbon oxides.

**Explosion Data**

<b>Sensitivity to Mechanical Impact</b>	Yes.
---	------

<b>Sensitivity to Static Discharge</b>	Yes.
--	------

**Protective equipment and precautions for firefighters**

Move containers from fire area if you can do it without risk. Damaged cylinders should be handled only by specialists.



## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

**Personal precautions** Stop leak if you can do it without risk.

**Other Information** Ventilate the area.

### Environmental precautions

**Environmental precautions** Prevent entry into waterways, sewers, basements or confined areas.

### Methods and material for containment and cleaning up

**Methods for containment** If possible, turn leaking containers so that gas escapes rather than liquid. Allow substance to evaporate.

**Methods for cleaning up** Do not direct water at spill or source of leak.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

**Handling** Handle in accordance with good industrial hygiene and safety practice. Do not puncture or incinerate cans. Contents under pressure. Avoid breathing vapors or mists. Avoid contact with eyes. Keep away from open flames, hot surfaces and sources of ignition.

### Conditions for safe storage, including any incompatibilities

**Storage** Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Protect from moisture. Keep out of the reach of children. Store away from other materials. Protect from sunlight. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations.

**Incompatible Products** Strong acids. Strong oxidizing agents. Strong bases.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

**Exposure Guidelines** The following ingredients are the only ingredients of the product above the cut-off level (or level that contributes to the hazard classification of the mixture) which have an exposure limit applicable in the region for which this safety data sheet is intended or other recommended limit. At this time, the other relevant constituents have no known exposure limits from the sources listed here



Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Hexanes 110-54-3	TWA: 50 ppm S*	TWA: 500 ppm TWA: 1800 mg/m <sup>3</sup> (vacated) TWA: 50 ppm (vacated) TWA: 180 mg/m <sup>3</sup>	IDLH: 1100 ppm TWA: 50 ppm TWA: 180 mg/m <sup>3</sup>
Acetone 67-64-1	STEL = 750 ppm TWA: 500 ppm	TWA: 1000 ppm TWA: 2400 mg/m <sup>3</sup> (vacated) TWA: 1800 mg/m <sup>3</sup> (vacated) TWA: 750 ppm (vacated) STEL: 1000 ppm (vacated) STEL: 2400 mg/m <sup>3</sup>	IDLH: 2500 ppm 10% LEL TWA: 250 ppm TWA: 590 mg/m <sup>3</sup>
Carbon Dioxide 124-38-9	STEL = 30000 ppm TWA: 5000 ppm	TWA: 5000 ppm TWA: 9000 mg/m <sup>3</sup> (vacated) TWA: 10000 ppm (vacated) TWA: 18000 mg/m <sup>3</sup> (vacated) STEL: 30000 ppm (vacated) STEL: 54000 mg/m <sup>3</sup>	IDLH: 40000 ppm TWA: 5000 ppm TWA: 9000 mg/m <sup>3</sup> STEL: 30000 ppm STEL: 54000 mg/m <sup>3</sup>
Cyclohexane 110-82-7	TWA: 100 ppm	TWA: 300 ppm TWA: 1050 mg/m <sup>3</sup> (vacated) TWA: 300 ppm (vacated) TWA: 1050 mg/m <sup>3</sup>	IDLH: 1300 ppm TWA: 300 ppm TWA: 1050 mg/m <sup>3</sup>

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits NIOSH IDLH Immediately Dangerous to Life or Health

**Other Exposure Guidelines** Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992) See section 15 for national exposure control parameters

**Appropriate engineering controls**

**Engineering Measures** Showers  
Eyewash stations  
Ventilation systems

**Individual protection measures, such as personal protective equipment**

**Eye/face protection** If splashes are likely to occur: None required for consumer use. Tight sealing safety goggles.

**Skin and body protection** Wear protective gloves and protective clothing. Long sleeved clothing. Impervious gloves. Chemical resistant apron. Antistatic boots.

**Respiratory protection** No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

**Hygiene Measures** Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**Physical and Chemical Properties**

<b>Physical state</b>	Liquid spray, Aerosol	<b>Odor</b>	Aliphatic hydrocarbons
<b>Appearance</b>	Clear	<b>Odor Threshold</b>	No information available
<b>Color</b>	No information available		



<u>Property</u>	<u>Values</u>	<u>Remarks</u>	<u>Method</u>
pH	UNKNOWN		
Melting / freezing point	No data available	None known	
Boiling point / boiling range	No data available	None known	
Flash Point	No data available	None known	
Evaporation Rate	No data available	None known	
Flammability (solid, gas)	No data available	None known	
Flammability Limit in Air			
Upper flammability limit	No data available		
Lower flammability limit	No data available		
Vapor pressure	No data available	None known	
Vapor density	No data available	None known	
Specific Gravity	0.71		
Water Solubility	Miscible in water		
Solubility in other solvents	No data available	None known	
Partition coefficient: n-octanol/water	No information available		
Autoignition temperature	No data available	None known	
Decomposition temperature	No data available	None known	
Kinematic viscosity	No data available	None known	
Dynamic viscosity	No data available	None known	
Explosive properties	No data available		
Oxidizing properties	No data available		
 <u>Other Information</u>			
Softening Point	No data available		
VOC Content (%)	No data available		
Particle Size	No data available		
Particle Size Distribution			

## 10. STABILITY AND REACTIVITY

### Reactivity

No data available.

### Chemical stability

Stable under recommended storage conditions.

### Possibility of Hazardous Reactions

None under normal processing.

### Hazardous Polymerization

Hazardous polymerization does not occur.

### Conditions to avoid

Heat, flames and sparks. Excessive heat.

### Incompatible materials

Strong acids. Strong oxidizing agents. Strong bases.

### Hazardous Decomposition Products

Carbon oxides.

## 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

#### Product Information

##### **Inhalation**

Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract. Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. May cause drowsiness or dizziness.

##### **Eye contact**

Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). May cause redness, itching, and pain. May cause irritation.

##### **Skin contact**

Specific test data for the substance or mixture is not available. Causes skin irritation. (based on components). Prolonged contact may cause redness and irritation. Repeated exposure may cause skin dryness or cracking.

##### **Ingestion**

Specific test data for the substance or mixture is not available. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways.

#### Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50



Hexanes 110-54-3	= 25 g/kg ( Rat )	= 3000 mg/kg ( Rabbit )	= 48000 ppm ( Rat ) 4 h
Acetone 67-64-1	= 5800 mg/kg ( Rat )	> 15700 mg/kg ( Rabbit )	= 50100 mg/m <sup>3</sup> ( Rat ) 8 h
Cyclohexane 110-82-7	= 12705 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	> 9500 ppm ( Rat ) 4 h

**Information on toxicological effects**

**Symptoms** Erythema (skin redness). May cause redness and tearing of the eyes. Difficulty in breathing. Coughing and/ or wheezing. Asthma-like and/ or skin allergy-like symptoms. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Sensitization** No information available.

**Mutagenic Effects** No information available.

**Carcinogenicity** Contains no ingredient listed as a carcinogen.

**Reproductive toxicity** Contains a known or suspected reproductive toxin.

**STOT - single exposure** Central nervous system (CNS).

**STOT - repeated exposure** Causes damage to organs through prolonged or repeated exposure. Based on classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200), this product has been determined to cause systemic target organ toxicity from chronic or repeated exposure. (STOT RE).

**Chronic Toxicity** Contains a known or suspected reproductive toxin. Possible risk of irreversible effects. Aspiration may cause pulmonary edema and pneumonitis. Avoid repeated exposure. Prolonged exposure may cause chronic effects.

**Target Organ Effects** Respiratory system. Eyes. Skin. Reproductive System. Central Nervous System (CNS). Central Vascular System (CVS). Peripheral Nervous System (PNS). Cardiovascular system. Digestive System. Gastrointestinal tract (GI).

**Aspiration Hazard** May be fatal if swallowed and enters airways.

**Numerical measures of toxicity Product Information**

The following values are calculated based on chapter 3.1 of the GHS document

- ATEmix (oral)**  
10,568.40 mg/kg
- ATEmix (dermal)**  
6,342.90 mg/kg (ATE)
- ATEmix (inhalation-dust/mist)**  
231.70 mg/l
- ATEmix (inhalation-vapor)**  
357.67 ATEmix



**12. ECOLOGICAL INFORMATION**

This product contains a chemical which is listed as a marine pollutant according to DOT

**Ecotoxicity**

Toxic to aquatic life with long lasting effects.

Chemical name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Hexanes 110-54-3		96h LC50: 2.1 - 2.98 mg/L (Pimephales promelas)		24h EC50: > 1000 mg/L
Acetone 67-64-1		96h LC50: 6210 - 8120 mg/L (Pimephales promelas) 96h LC50: = 8300 mg/L (Lepomis macrochirus) 96h LC50: 4.74 - 6.33 mL/L (Oncorhynchus mykiss)	EC50 = 14500 mg/L 15 min	48h EC50: 12600 - 12700 mg/L 48h EC50: 10294 - 17704 mg/L
Cyclohexane 110-82-7	72h EC50: > 500 mg/L (Desmodesmus subspicatus)	96h LC50: 3.96 - 5.18 mg/L (Pimephales promelas) 96h LC50: 48.87 - 68.76 mg/L (Poecilia reticulata) 96h LC50: 24.99 - 44.69 mg/L (Lepomis macrochirus) 96h LC50: 23.03 - 42.07 mg/L (Pimephales promelas)	EC50 = 85.5 mg/L 5 min EC50 = 93 mg/L 10 min	24h EC50: > 400 mg/L

**Persistence and Degradability**

No information available.

**Bioaccumulation**

Chemical name	Log Pow
Acetone 67-64-1	-0.24
Cyclohexane 110-82-7	3.44

**Other adverse effects**

No information available.



**13. DISPOSAL CONSIDERATIONS**

**Waste treatment methods**

**Disposal methods** This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

**Contaminated Packaging** Dispose of contents/containers in accordance with local regulations.

**US EPA Waste Number** D001 U056 U002

**California Waste Codes** 331

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical name	California Hazardous Waste
Hexanes 110-54-3	Toxic Ignitable
Acetone 67-64-1	Ignitable
Cyclohexane 110-82-7	Toxic Ignitable

**14. TRANSPORT INFORMATION**

**DOT**

**Proper Shipping Name** CONSUMER COMMODITY  
**Hazard Class** ORM-D  
**Marine Pollutant** This product contains a chemical which is listed as a marine pollutant according to DOT  
**Description** CONSUMER COMMODITY, ORM-D  
**Emergency Response Guide Number** 126

**TDG**

**UN-No.** UN1950  
**Proper Shipping Name** AEROSOLS  
**Hazard Class** 2.1  
**Description** UN1950, AEROSOLS, 2.1

**MEX**

**UN-No.** UN1950  
**Proper Shipping Name** AEROSOLS  
**Hazard Class** 2.1  
**Description** UN1950, AEROSOLS, 2.1

**ICAO**

**UN-No.** UN1950  
**Proper Shipping Name** AEROSOLS  
**Hazard Class** 2.1  
**Description** UN1950, AEROSOLS, 2.1

**IATA**



**UN-No.** UN1950  
**Proper Shipping Name** AEROSOLS, FLAMMABLE  
**Hazard Class** 2.1  
**ERG Code** 10L  
**Description** UN1950, AEROSOLS, FLAMMABLE, 2.1

**IMDG/IMO**

**UN-No.** UN1950  
**Proper Shipping Name** AEROSOLS  
**Hazard Class** 2.1  
**EmS-No.** F-D, S-U  
**Marine Pollutant** This product contains a chemical which is listed as a marine pollutant according to IMDG/IMO  
**Description** UN1950, AEROSOLS (HEXANES), 2.1, MARINE POLLUTANT

**RID**

**UN-No.** UN1950  
**Proper Shipping Name** AEROSOLS  
**Hazard Class** 2.1  
**Classification code** 5F  
**Description** UN1950, AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS  
**ADR/RID-Labels** 2.1

**ADR**

**UN-No.** UN1950  
**Proper Shipping Name** AEROSOLS  
**Hazard Class** 2.1  
**Classification code** 5F  
**Tunnel restriction code** (D)  
**Description** UN1950, AEROSOLS, 2.1, (D), ENVIRONMENTALLY HAZARDOUS

**ADN**

**UN-No.** UN1950  
**Proper Shipping Name** AEROSOLS  
**Hazard Class** 2.1  
**Classification code** 5F  
**Special Provisions** 190, 327, 344, 625  
**Description** UN1950, AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS  
**Hazard Labels** 2.1  
**Limited Quantity** 1 L  
**Ventilation** VE01, VE04

**15. REGULATORY INFORMATION**

**International Inventories**

TSCA Not determined  
 DSL Not determined  
 IECSC

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory  
 DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

**US Federal Regulations**

**SARA 313**



Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No.	Weight-%	SARA 313 - Threshold Values %
Hexanes - 110-54-3	110-54-3	30 - 60	1.0
Cyclohexane - 110-82-7	110-82-7	1 - 5	1.0

**SARA 311/312 Hazard Categories**

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications. Under the amended regulations at 40 CFR 370, EPCRA 311/312 Tier II reporting for the 2017 calendar year will need to be consistent with updated hazard classifications.

**CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Cyclohexane 110-82-7	1000 lb			X

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Hexanes 110-54-3	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Acetone 67-64-1	5000 lb		RQ= 2270 kg final RQ RQ= 5000 lb final RQ
Cyclohexane 110-82-7	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

**US State Regulations**

**California Proposition 65**

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65
Hexanes - 110-54-3	Male Reproductive

**U.S. State Right-to-Know Regulations**

Chemical name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Hexanes 110-54-3	X	X	X	X	X
Acetone 67-64-1	X	X	X	X	
Carbon Dioxide 124-38-9	X	X	X		-
Cyclohexane 110-82-7	X	X	X	X	

**International Regulations**

**Mexico**

**National occupational exposure limits**

Chemical name	Carcinogen Status	Exposure Limits
Hexanes		Mexico: TWA 50 ppm



		Mexico: TWA 176 mg/m <sup>3</sup> Mexico: STEL 1000 ppm Mexico: STEL 3500 mg/m <sup>3</sup>
Acetone		Mexico: TWA= 1000 ppm Mexico: TWA= 2400 mg/m <sup>3</sup> Mexico: STEL= 1260 ppm Mexico: STEL= 3000 mg/m <sup>3</sup>
Carbon Dioxide	-	Mexico: TWA= 5000 ppm Mexico: TWA= 9000 mg/m <sup>3</sup> Mexico: STEL= 15000 ppm Mexico: STEL= 27000 mg/m <sup>3</sup>
Cyclohexane		Mexico: TWA 300 ppm Mexico: TWA 1050 mg/m <sup>3</sup> Mexico: STEL 375 ppm Mexico: STEL 1300 mg/m <sup>3</sup>

Mexico - Occupational Exposure Limits - Carcinogens

**Canada**  
**WHMIS Hazard Class**  
Not determined

**16. OTHER INFORMATION**

<b>NFPA</b>	<b>Health Hazards</b> 2	<b>Flammability</b> 4	<b>Instability</b> 0	<b>Physical and Chemical Hazards</b> -
<b>HMIS</b>	<b>Health Hazards</b> 2 *	<b>Flammability</b> 4	<b>Physical Hazard</b> 0	<b>Personal Protection</b> X

**Chronic Hazard Star Legend** \* = Chronic Health Hazard

**Prepared By** Maverick Performance Products  
5950 S Cooper Road  
Chandler, AZ 85249  
(480) 621-7302

**Issuing Date** 06-Feb-2019  
**Revision Date** 15-June-2020  
**Revision Note** No information available

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal, and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**

